

Groupe manufacturier d'ascenseurs



GLOBAL TARDIF

Elevator Manufacturing Group

120 rue de Naples, St Augustin de
Desmaures, Qc, Canada, G3A 2Y2
P. 418.878.4116 F. 418.878.1595 Email :
info@globaltardif.com

GT100C HD Commercial Wheelchair Lift **CSA** B355-09 & ASME A.18.1

REQUEST FOR PRICING (RFP) GT Accessibility Update: 2011-05-31

Date : _____

Estimate #: _____

To be completed by Global Tardif

Company Name : _____

Job Name : _____

Contact name: _____

Location : _____

Telephone : _____

Fax : _____

NOTE: All completed RFP's can be either faxed to 418.878.1595 or emailed to info@globaltardif.com

General Information: Please visit our web at www.gtaccessibility.com for additional information

Applicable Codes including Local : _____

1.0 Model Base Package

☐ GT100C Heavy Duty Base package (KV1P down speed only)

Base package include Complete Structural hydraulic 2:1 package, complete power unit with screw submersible pump and single speed control valve KV1P, constant pressure operation. (NO CAB)

1.1 Number of Stops

☐ 2 Stops

☐ 3 Stops

☐ Other number of stops _____

1.2 Voltage

☐ Voltage for Motor & Control **STANDARD** 220 V / 1 / 60

☐ Voltage for Motor & Control 575-600 V / 3 / 60

☐ Voltage for Motor & Control 208 or 480 V / 3 / 60

1.3 Capacity

☐ 1000 lbs max @ 30 fpm

1.4 Pit Depth

☐ Standard 10" (254 mm)

☐ Other: Specified: _____ Inches

1.5 Overhead (minimum 92" for 80" high cab - if higher cab, add same increase in overhead)

☐ Standard minimum 96" (2438 mm)

☐ Overhead: Other Confirm exact dimension : _____

1.6 Total Travel

☐ = total travel height in INCHES

1.7 Guide Rails Sections

☐ 8 ft rail section **STANDARD**

☐ 16 ft rail section

1.9 Machine room layout

☐	Adjacent Machine Room
☐	Opposite Machine Room
☐	Rear Machine Room
☐	Remote Control Room

Specified: feet Customer must provide a sketch for our engineering dept.

2.0 CAB

2.1 Configuration Model Type

☐	GT 101 (Front only)	☐	GT 102 (Front/Rear)	☐	GT 103 (Front/Side)	☐	GT 104 (Side only)
--------------------------	---------------------	--------------------------	---------------------	--------------------------	---------------------	--------------------------	--------------------

2.2 Cab Size

(all dimensions are approx. & may vary with the models selected)

Standard size	GT 101C	GT 102C	GT 103C	GT 104C
Cab, size (WxD)	36" x 62"	36" x 63"	36" x 60"	60" x 36"
Hoistway size (WxD)	54" x 65"	54" x 64"	54" x 66"	68" x 54"
Other size up to 21 Sq. ft (where permitted)	Confirm cab size : W: inches D: inches			
	Confirm hoistway size : W: inches D: inches			

2.3 CAB Height

☐	1	Standard 6'-8" cab height
☐		Optional Custom cab height up to 8'-0" Confirm exact cab height :

**** if higher cab is required, additional clear overhead of same increase will be required also.**

2.4.0 CAB Inside fFinish

☐	M Serie - Melamine Panels Serie 3/4" melamine panels, ceiling is white melamine with two (2) recessed pot light fixture and plastic eggcrate inserts
☐	Unfinished MDF Particule Board (Medium density)
☐	Standard Melamine Hardrock Maple # 992
☐	Standard Melamine Classic Cherry # 314
☐	Additional " add on " above Cab package selection above
☐	Hiteak # 511
☐	Sweet Beige # 520
☐	Bryan Maple # 687
☐	Inspiration # 744
☐	Urban Mahogany # 838
☐	Sheen Linen # G20
☐	Coastal Pear # G23

☐	PL Serie - Plastic Laminate Panels Serie 3/4" plastic laminate panels, ceiling is white melamine with two (2) recessed pot light fixture and plastic eggcrate inserts
☐	Global Tardif Standard Wilsonhart Plastic Laminate selection Chart (32 colors)
☐	Other Wilsonart Plastic laminates (overall choice 240)
☐	Custom Plastic Lam. or any other special cab walls finishes
☐	Other Standard plastic laminate - Max. \$ 4.00 per Sq. ft
☐	Custom Plastic Laminate or any other special cab walls finishes

Specify:	
Specify:	
Specify:	
Specify:	

Additional Cab Wall Options

☐	Glass Wall - Side or Rear wall w/ clear Lam. Safety glass - Aluminum framing
☐	Glass Wall - Side or Rear wall w/ clearLam. Safety glass with stainless # 4 framing
☐	Glass Wall - Side or Rear wall w/ clear Lam. Safety glass stainless # 8 framin
☐	Glass Wall - Side or Rear wall w/ clear Lam. Safety glass Satin Bronze framir
☐	Optional " Mirror panel " - Above handrail height - per mirro

2.4.1 Cab Ceiling and Cab lighting

☐	Standard white melamine with (2) pot lights
☐	Optional Bronze pot lights instead of typical white trim

2.4.2 CAB Handrails

☐	Standard	Handrail - Standard - St/Stl #4 Tubular 1 1/4" - 18" LG
☐	Optional	Flat handrail 1/4" x 2" Stainless steel # 4
☐	Optional	Flat handrail 1/4" x 2" Bronze # 4
☐	Optional	Tubular 1 1/2" Stainless # 4 - Black flat end caps
☐	Optional	Tubular 1 1/2" Polished Stainless # 8 Mirror finish - Black flat end caps
☐	Optional	Tubular 1 1/2" Bronze satin # 4 - Black flat end caps
☐	Optional	Tubular 1 1/2" Bronze Mirror - Flat end caps

2.4.5 CAB Flooring

☐	Standard	Unfinished Plywood - Two (2) layers - 1 1/4" thick total
☐	Optional	Hardwood floor (Dark or light oak, maple)
☐		Rubber mat flooring - Amtico

3.0 Landing Swing door

☐	Manual CEITA GT-EZ Swing Door -Series GT-C10 - Standard Duty -fire rated 1 1/2 hr Zinc coated w/ vision glass, closers , Prudhomme roller & arm lock similar to GAL - 36" (914mm) x 80" (2032 mm)
☐	Manual GT-EZ Swing door -Series GT-MT01 - HEAVY DUTY – fire rated 1 1/2 hr Zinc coated w/ vision glass, closers , GAL Type N lock - 36" (914mm) x 80" (2032 mm)

3.1 Custom entrances & Options

☐	GT-Swing Door	***	Alu. Frame	Plexiglass insert	Prud'homme lock	36" (914mm)
☐	GT-Swing Door	***	Alu. Frame	Lexan insert	Prud'homme lock	36" (914mm)
☐	GT-Swing Door	***	Alu. Frame	Tempered/ Lam Glass	Prud'homme lock	36" (914mm)
☐	Additional Cost to provide " Clear anodized Aluminum " GT Swing Door framing					
☐	Custom GT Swing door - St/Stl # 4 framing with laminated glass & pivots at top & bottom, w/ hydraulic closer on surface, GAL Type " N" Lock - 36" (914mm) x 80" (2032 mm)					
☐	FRAMELESS Glass Custom GT Swing door - Laminated/Tempered glass & pivots at top & bottom, with hydraulic closer on surface, Prud'home Lock - 36" (914mm) x 80" (2032 mm)					
☐	Motorized Retiring Cam for intermediate level. (Not required by Code)					

3.2 Landing door options

☐	Option to provide - Stainless steel kick plate at bottom of door, hoistway side only					
☐	Custom paint color * <i>For GT-Swing Door or GT-Swing Gate</i>					
☐	Brass kickplate and push plate (instead of stainless)					
☐	Aluminum checker plate sill ** <i>Available only with our HEAVY DUTY swing door</i>					
☐	GAL Key to Unlock the Interlock					
☐	GAL type "N" Interlock ONLY When landing entrances are provided by others					
☐	Prud'homme " Electric Strike" ONLY When landing entrances are provided by others					
☐	Automatic door operator - On surface for full size doors Hunter/ Portronik # 4200					
☐	Closer door operator- Recessed in flooring					
☐	If other specify:					

4.1 Controller options

☐	UPS Emergency Battery Lowering (included in base package)
☐	Short Floor - Floor to floor lower than 12"
☐	" Up" start counter
☐	Automatic " turn off " cab lighting

5.0 ELECTRICAL EQUIPMENT

☐	Travelling cable Not required - provided by others
☐	Travelling cable provided by GT
☐	Electrical Wiring Not required - provided by others
☐	Electrical wiring material provided by GT
☐	Electrical Conduit Not required - provided by others
☐	Electrical Conduit & junction boxes (EMT & Duct) provided by GT

6.0 Type of Power unit

- ☐ Standard " NONE SUBMERSIBLE MOTOR " with submersible pump
☐ If " SUBMERSIBLE MOTOR " instead of dry motor w/ submersible pump

6.1 Hydraulic Valve option

- ☐ Multi-Speed valve - Slow Up & Down speed EV100 valve

6.2 Hydraulic Oil

- ☐ Not required - provided by others
☐ Hydraulic Oil supplied by GT **

*** GT will not ship to Canada or US any hydraulic oil - Only pick up at the plant*

6.3 Hydraulic hose line & fittings

- ☐ Not required - provided by others
☐ Hydraulic hose line, fittings & flow control provided by GT

7.0 FIXTURES

All Car Operating Panel (C.O.P.) include emergency car lighting, floor selection buttons, Stop & Alarm push button.
All hall stations are surface mount and contain " In Use " light and "

- ☐ Standard COP
☐ Optional Digital Car Position Indicator - Dot matrix
☐ Optional Rear Opening provision for button operation.
☐ Optional Brass COP and pushbuttons

7.1 Telephone

- ☐ Standard telephone box (no phone) Stainless # 4: ☐ Bronze # 4: ☐ Specify:
☐ Hands Free phone Integrated in COP

7.2 Hall Stations (specify number of:)

- ☐ Standard Keyless Call push button
☐ Keyless Call push button & Car here indicator
☐ Keyed Call station & Car here indicator
☐ Add On - OFF key
☐ Add " Door Open " if Automatic
☐ Add wheelchair " logo " on faceplate

8.0 MISCELLANEOUS

8.1 Fasteners for rail brackets - Select only one (1= Yes)

- ☐ Not required **STANDARD**
Concrete anchors ☐ Lag bolts ☐ Through Bolts ☐ Specify with an "X"

8.2 Other Miscellaneous

- ☐ Pre-Cut & Washed rails
☐ Split Cylinder Up-charges

9.0 CRATING

- ☐ Un-crated material - Pick up by Elevator Contractor at our plant
☐ Crating on a pallet
☐ Crating in a wood box - totally enclosed with plastic wrap protection
☐ Overseas Crating - wood treated

Clarifications, Comments or Alternate
